

# S100B

Compact QWERTY  
Programmable Keyboard Series



# S100B

## Compact QWERTY Programmable Keyboard Series



### Key Features

- Compact Full keyboard layouts, with programmable keys
- High quality membrane keys with tactile feeling
- Laser-engraved keycap symbols or high quality UV silk screen printed keycap symbols
- Damaged keys can be easily replaced and hence save the replacement cost
- With internal strong metal plate to enhance the protection against ESD is increased
- Different relegendable keycaps (1-fold, 2 fold) are available
- Detachable cable, using RJ-45 connector
- Extended SCR, MICR and Customer Display are available as optional plug-in modules
- All are equipped with 3-track MSR

### Technical Data

#### [Electronics]

##### Power supply

PS/2: +5V/DC  $\pm 10\%$

USB: +5V/DC  $\pm 5\%$

##### Current input

PS/2: <100mA

USB: <100mA

#### [Others]

Storage temperature: -40°C to +60°C

Operating temperature: 0°C to +50°C

Operating humidity: 20% to 90%

Dimension (LxWxH, mm): 410 x 167 x 50

Weight (g): 1320

#### [Mechanical]

Total travel: 4 - 0.4mm

Pre-travel: 2  $\pm 0.6$ mm

Peak load before make: 60  $\pm 20$ cN

### MICR Reader Feature

- Powered by Magtek module
- Reads MICR characters on checks, deposit, withdrawal slips, and other MICR encoded documents
- RS-232/USB interface
- Reads E13-B and CMC-7 MICR fonts
- With external power adaptor, 12V-AC, 18W, 1A

### Programmable Features

- All keys can be programmed with unlimited characters
- All data can be retained for no less than 100 years without additional battery
- Does not require a TSR program and hence avoids application software crashes
- Provides multi-level programming
- Provides for a variable time delay of up to 255 seconds in each programmed string
- Provides true keyboard wedge function that operates with or without the normal computer keyboard connected
- Provide a true Caps/Scroll/Numeric Lock function independent of any other keyboards being connected
- Support PS/2 programming in DOS, Windows9X, Me, 2K, XP

### MagStripe Reader Features

- Comply with ISO 7812, IBM standards, AAMVA, JIS-2
- Support multi-country code settings
- Support programmable MSR setting for the header, tailor, separator, suffix and prefix, track sequence
- Track 1: 210BPI with max 76 characters
- Track 2: 210BPI with max 107 characters or 75BPI with max 37 characters
- Track 3: 210BPI with max 107 characters
- Card swipe speed: 10 to 100 cm/s
- 500,000 swipe cycles
- Speed: 3-125 ips at 75 BPI; 3-50 ips at 210 BPI

### SmartCard Reader Features

- T=1, T=0 protocol support; Memory card support through SCM MCARD API
- Communication speed up to 344,105 bps (PPS, FI parameter)
- Frequency up to 12 MHz (PPS, DI parameter)
- Support ISO 7816 Class A and AB smart card
- Sliding contact connector; Certified for 200,000 insertions
- Support PC/SC, CT-API (thru wrapper on top of PC/SC); OCF upon request
- Full speed USB (12Mbps); Bus powered device; CCID compliant

#### Interface

P:PS/2

U:USB

#### Model Configuration

S100B-X-XX-XXXX

#### Operator Display

202V: 20\*2 characters top extended VFD Display

204V: 20\*4 characters top extended VFD Display

#### Extended SCR/MICR Plug-in modules

NN: not installed

S1: with extended pure SCR reader

C1: with extended pure MICR reader

C2: with extended MICR and SCR reader

**HENG YU**

**Heng Yu Technology (Hong Kong) Limited**

Address : Room 1003-4, HSH MongKok Plaza, 500 Nathan Road,

Phone : (852)23941852 23941870 Web site : <http://www.hengyu.com>

Fax : (852)23941865

E mail : [hy\\_sales@hengyu.com](mailto:hy_sales@hengyu.com)



created using  
**BCL easyPDF**  
Printer Driver